

# TUBARÃO:



TERMINAL	LOADING RATE	MAX DRAFT (Mtrs)	Av. W/D
TPD 3	2.000 MT grain per hour (04 LOADERS)	15.00m	1.025

# VITÓRIA:

TERMINAL	LOADING RATE	MAX DRAFT (Mtrs)	Av. W/D
201	2.000 MT grain per hour (04 LOADERS)	12.60	BW 1.018 / 1.022
207		12.60	BW 1.018 / 1.022
905		9.00	BW 1.018 / 1.022

VITORIA CANAL MAX DRAFT: 10.67 meters

**Restrictions at Vitoria port canal access for TANKERS**

PORTE BRUTO MAX : 55.000 MT  
Water density 1.018 – 1.022 – BW

Max LOA: 244,99  
Max BEAM: 32.49  
Max airdraft: 48 M (in order to cross the bridge)  
Max draft: 10.60 M plus tide (to maneuver during daylight)

**Restrictions at Vitoria port canal access during night time as follows:**

**For berthing maneuver:**  
Max LOA: 205,99  
Max BEAM: 32.49  
Max airdraft: 48 M (in order to cross the bridge)  
Max draft: 10.20 M plus tide – restricted to max 11.30 M considering tide

**For sailing maneuver:**  
Max LOA: 205,99  
Max BEAM: 32.49  
Max airdraft: 48 M (in order to cross the bridge)  
Max draft: 10.60 M plus tide – restricted to max 11.75 M considering tide

Max LOA: from 206,00 up to 220,99  
Max BEAM: 32.49  
Max airdraft: 48 M (in order to cross the bridge)  
Max draft: 10.60 M plus tide – restricted to max 10.85 M considering tide

